

Bright steel wire



- Soft steel wire, uncoated, drawn in accordance with Standard EN 10.016-2, C4D or C7D quality (other compositions are possible depending on the requirements of the customer).
- Suitable for bending and soldering as well as for paint, electrolytic zinc and chrome treatments.
- Dead cast wire suitable for use in CNC machines
- Diameters from 2.00 to 12.00 mm
- Coils of 500 to 2,500 kg



Table of general resistances

Diameter (mm)	R _{min} (N/mm ²)	R _{max} (N/mm ²)
3	760	840
4	620	700
5	540	710
6	520	680
7	510	670
8	500	650
9	490	640
10	480	610
11	480	610
12	470	600

Coil dimensions

Ø Wire (mm)	Weight (kg)	Ø interior (mm)	Ø exterior (mm)	h (mm)
3,0 - 3,4	500 - 1000	500	< 800	400
3,9 - 12	500 - 1500	550	< 900	520
3,9 - 12	1000 - 2500	550	< 1200	600
3,9 - 12	1000 - 2500	550	< 1000	670



Exel Fil, S.A.
Apdo. de Correos 129
Polígono Industrial s/n
25200 Cervera (Spain)
Tel. + (34) 97 353 22 12
Fax + (34) 97 353 28 09
exelfil@exelfil.com
www.exelfil.com

Sales office / Export
Ganduxer, 127 bajos
08022 Barcelona (Spain)
Tel. + (34) 93 253 17 22
Fax + (34) 93 253 05 83
export@exelfil.com
www.exelfil.com